



UUKi UK – Israel innovation researcher mobility scheme(call 2)

Guidelines

**DEADLINE EXTENDED: Tuesday 30 January 2024
5pm (GMT)**

Navigate to:

1. Background and overview of the scheme 2
- 2.



1. Background and overview of the scheme

Universities UK International (UKI) operating unit of Universities UK, is a mobility scheme provides funding for researchers and research related staff from UK, Israeli and other higher education institutions (HEIs) to spend.

un82.2 (r)31.4 (a)0.6 (u)-9 (r(U)-8.3r)-5.9 (l)-10.4.006 Tw (n)-4.8 ()JTJ 0.(v)-8.6 (n)-4.8 (o)-3.7 (v(-



- x Support UKHEIs to further their existing and develop new partnerships with higher education institutions or companies in



the innovation and/or entrepreneurship development of the researchers and the research community in the UK more widely.

To be eligible to undertake periods of mobility, researchers and research related staff must:

- x For Lead UK HEI: be employed or be undertaking a research degree (PhD, MRes or equivalent) at UK HEI for the duration of the mobility
- x For partner organisation: be employed or be undertaking a research degree (PhD, MRes or equivalent) at partner organisation for the duration of the mobility
- x Be able to undertake mobility within the timeframe 1 April 2024 – 31 January 2025.

In order to carry out their project, those receiving funding must undertake their full months of mobility by being physically located in the country that they are receiving the mobility funding for

4. Available funding

This is the second and final call of this two-year programme. The total amount of funding available for UK Israel innovation



Indirect cost (contribution to the UK Lead HEI)

Set at 10% of Direct costs Set at 10% of Direct





15. Applicant Eligibility checklist

The application form is completed in full and complies with instructions given

The budget spreadsheet has been completed and sent to the email address listed

above upon submission of the online application 658.08 382.2 17.52 re W n BT /TT4 1 Tf -0.003 Tc n BT /TT6 (m)-5.5 (a)0.6